

9

MAR-14-03

03:53PM FROM-Fenwick & West

416 281 1360

T-531 P.031/054 F-053

公開実用 昭和57 - 6296



実用新案登録願(3)

55. 6. 12

昭和 年 月 日

(4. 満円)

特許庁長官 殿

- 1 考案の名称 引き出し形ファンユニット構造
- 2 考案者  
居 所 東京都港区虎ノ門1丁目7番12号  
沖電気工業株式会社内  
氏 名 阿部正平 (外1名)
- 3 実用新案登録出願人  
住 所(〒-105) 東京都港区虎ノ門1丁目7番12号  
名 称(029) 沖電気工業株式会社  
代表者 三宅正男
- 4 代理人  
居 所(〒-105) 東京都港区虎ノ門1丁目7番12号  
沖電気工業株式会社内  
氏 名(6892) 弁理士 鈴木敏明  
電話 (501)3111 大代表



55 031000

6296

方式  
審査




9

MAR-14-03 03:53PM FROM-Farwick & West

415 261 1350

T-931 P.032/054 F-693

# 第 1 図



6296 <sup>1</sup>/<sub>4</sub>

実用新案登録出願人 沖電気工業株式会社

代理人 鈴木敏明


9

MAR-14-03 03:53PM FROM-Fenwick & West

416 281 1360

T-531 P.033/034 F-053

第 3 図



6.7.06  $\frac{3}{4}$

実用新案登録出願人 神電氣工業株式会社

代理人 鈴木 敏 明

9

(19) Patent Office of Japan (JP)

(11) Laid-Open Utility Model Application Publication

(12) Official Gazette for Utility Model Publications (U)

**Kokai U57-6296**

(51) Int. Cl.<sup>3</sup> ID No. Internal Office No. (43) Kokai Publication Date: 01.13.82  
H05 K 7/20 6428-5F  
5/02 6332-5F

Request for Examination: not yet submitted  
(Total number of pages in the original: 3)

(54) Title of the Innovation\*: STRUCTURE OF AN EXHAUST-TYPE FAN UNIT

(21) Utility Model Application No. 55-81000

(22) Utility Model Application Date: 06.12.80

(72) Innovator\*: Masahira Abe

Okidenki Kogyo Co., Ltd.

1-7-12, Toranomom, Minato-ku, Tokyo.

(72) Innovator\*: Tsutomu Tagooka

Okidenki Kogyo Co., Ltd.

1-7-12, Toranomom, Minato-ku, Tokyo

(71) Applicant: Okidenki Kogyo Co., Ltd.

1-7-12, Toranomom, Minato-ku, Tokyo

(74) Agent: Toshiaki Suzuki, Patent Attorney

(57) Claims

A structure of an exhaust-type fan unit 11 intended for positively cooling an electronic device, said fan unit having an air-intake port located in the lower part of the electronic device housing 9, an air-discharge port in the upper part of said housing, and an air-flow duct formed in the upper part of the housing for guiding the air flow and for removal of heat, said structure being characterized by comprising: an upper guide rail 11d and a lower guide rail 1e installed on both side walls inside the fan unit housing 11a; a fan mounting plate 1b arranged between said guides with a sliding fit; a stopper 11f rigidly installed in a fixed position on the lower guide rail and having a construction that allows its withdrawing towards the rear side of the fan unit housing 11a; and a disconnectable cable duct 15a attached to the front side of said fan unit housing 11a.

#### Brief Description of the Drawings

Fig. 1 is a view of the known positive-cooling system for an electronic unit, where Fig. 1a is a front view, and Fig. 1b is a side view. Fig. 2 is a view of the positive-cooling system for an electronic unit according to the present innovation, where Fig. 2a is a front

-----  
\*The terms "innovator" and "innovation" are used instead of "inventor" and "invention" to emphasize that this document is a Utility Model and not a Utility Patent (translator's note)

view, and Fig.2b is a side view. Fig. 3 is a three-dimensional view of the fan-unit of the innovation. Fig. 4 is a sectional view along the line X-X of Fig. 3 . Fig. 5 is a sectional view along the line Y-Y of Fig. 3.

1a – fan unit housing; 1b – fan unit cover; 2 – fan; 3 – shelf; 4 – printed circuit board; 5a – cable duct; 5b – cable duct support frame; 6 – cable with a connector; 7 – back-side connector; 8 – wiring plate; 9 – housing; 11 – fan unit; 11a – fan unit housing; 11b – fan mounting plate; 11c – handle; 11d – upper guide rail; 11e – lower guide rail; 11f – stopper; 11g – fixing element; 11h – fan clamping device; 11j, 11k – screws; 15a – cable duct; 15b – screw.

Fig. 4

